



# LE1017

## FEATURES

- + Reliable performance
- + Sturdy design and easy operation
- + 17in 5-wire resistive touch panel
- + Automatic brightness control
- + Positive locking tilt angles
- + High contrast with 500:1 ratio
- + Built-in universal power supply
- + USB interface
- + VESA mount

## Touch Screen Monitor

The LE1017 17 inch touch monitor is built to meet the requirements that leading retailers and restaurant operators need from their Point of Sale system. With the 5-wire resistive touch panel, a high 500:1 contrast ratio and up to SXGA 1280X1024 resolution, the screen offers clear visibility for easy and efficient operations. The touch screen is highly rugged and stable, built for continuous use. The unit includes a solid base and a locking tilt mechanism so that the angle of the touch screen does not change usage.



# LE1017 specifications

## LCD TOUCH PANEL

LCD size:	17in (43.1cm)
Brightness:	300
Response time:	8ms.
Contrast ratio:	500:1
Resolution:	SXGA (1280 x 1024)
Viewing angle:	150° / 130°
Touch screen:	5 Wire Resistive Touch Panel   USB interface

## MECHANICAL

Net Weight:	11.7lbs ± 1 / 12.1lbs ± 1
Dimensions (WxHxD):	Without stand: 1.5in x 1.4in x .6in (38.6cm x 37.2cm x 17.1cm)
With stand:	1.5in x 1.5in x .9in (38.6cm x 39.6cm x 23.5cm)
Color:	Black

## ELECTRICAL

Power supply:	Built-in Universal Power Supply   100-240 VAC, 50/60 Hz
Power consumption:	Active < 48 Watt Max.
Saving mode:	Standby < 3 Watt

## ENVIRONMENTAL

Operating temperature:	32°F to 113°F (0°C to 45°C)
Storage temperature:	68°F to 140°F (20°C to 60°C) for standard LCDs
Humidity:	10~90% non-condensing

## MISCELLANEOUS

Plug & Play, Kensington Lock Support, VESA DDC 2B compatible.  
Speaker, Touch and Light Sensor are optional.